



Partition Stalls

Maintenance Guide

 646-453-4564

 info@partitionstalls.com

 www.partitionstalls.com

SOLID PLASTIC Toilet Partitions

Maintenance Procedure

1 . 0 1 **Solid Plastic**

Maintenance of your toilet partitions should be a part of your regular building preventive maintenance procedure.

- 1 Tighten any screws that have become loose due to vibrational forces or attempted vandalism.
- 2 Be sure the surfaces are dry after being cleaned and rinsed with clear water (when required).
- 3 Partitions exposed to severe humidity should be washed and dried as needed.
- 4 Periodically, remove any dirt, grime or foreign matter with a soft cloth.
- 5 Where surfaces reveal spotting resulting from hand perspiration, soil, or grease, a thorough cleaning with warm water and a mild detergent (i.e. Ivory Soap), followed by rinsing, and removal of excess moisture, will renew the clean even surface, providing a pleasant sanitary appearance. (Use of cleaning agents containing abrasives such as household cleaning powder, steel wool, and harsh detergents or acids ARE NOT RECOMMENDED).
- 6 For areas of stubborn graffiti, commercial graffiti removers can be used.
- 7 To maintain the brilliance of hardware, these components can be periodically improved by an application of non-abrasive cleaner with a damp cloth.
- 8 If your partitions have a continuous hinge, regular application of an LPS II or an industrial type, non-drying lubricant is recommended.
- 9 The appearance of scratches may be minimized by burnishing the blemish with a smooth, rounded object such as a spoon. For best results, apply slight pressure in a parallel motion to the scratch.

